

COMMONWEALTH UTILITIES CORPORATION**CUC - RFP - 19 - 007**

| ITEM | SPECIFICATIONS |
|--|-----------------------------------|
| POLE, CONCRETE, 35 - CLASS I | SEE SPECIFICATIONS |
| POLE, CONCRETE, 40 - CLASS I | SEE SPECIFICATIONS |
| POLE, CONCRETE, 45' - CLASS I | SEE SPECIFICATIONS |
| POLE, CONCRETE, 55' - CLASS 1 | SEE SPECIFICATIONS |
| POLE, WOOD, ACA TREATED, 35' - CLASS 1 | SEE SPECIFICATIONS |
| POLE, WOOD, 40' - CLASS 1 | SEE SPECIFICATIONS |
| CROSSARM WOOD, 3-3/4X4-3/4X 8' | SEE SPECIFICATIONS |
| CROSSARM, WOOD, 3-3/4 X 4-3/4 X 10' | SEE SPECIFICATIONS |
| BRACE, CROSSARM, STEEL 60" SPAN X 18" DR | SEE SPECIFICATIONS |
| INSULATOR, PIN TYPE, 56-1, 1-3/8, 23KV | LAPP 8248R-70, PLH P56-1G |
| INSULATOR, DEADEND, POLYMER, 25 KV | OHIO BRASS 401028-0215, REL DS28G |
| INSULATOR, SPOOL, 3" | JOSLYN J101, PLH P53-1G |
| PIN, POLE TOP, STRAIGHT, 1-3/8, 15" FIBER | JOSLYN 7561-615NTX, CHANCE RPM152 |
| BOLT, CARRIAGE, 1/2 X 6" | JOSLYN J8646 |
| BOLT, MACHINE, 1/2X6" | JOSLYN J8705, CHANCE 8705 |
| BOLT, MACHINE, 3/4 X 14" | JOSLYN J8914 |
| BOLT, MACHINE, 3/4 X 16" | JOSLYN J8916 |
| BOLT, MACHINE, 5/8 X 12" | JOSLYN J8812 |
| BOLT, MACHINE, 5/8 X 14" | JOSLYN J8814 |
| BOLT, MACHINE, 5/8 X 16" | JOSLYN J8816 |
| BOLT, SINGLE UPSET, 5/8 X 18" | SEE SPECIFICATIONS |
| BOLT, EYE, OVAL, 5/8X12" | JOSLYN J9412, CHANCE 29962 |
| BOLT, EYE, OVAL, 5/8 X 14" | JOSLYN J9614, CHANCE 19784 |
| BOLT, EYE, OVAL, 3/4 X16" | JOSLYN J9616, CHANCE 19786 |
| NUT, OVAL EYE, 5/8 | JOSLYN J1092, CHANCE 6501 |
| FENDER WASHER, ROUND, 9/16 (1/2) | JOSLYN J1086 |
| WASHER, SQ, CURV, 3X3 (3/4) | JOSLYN J6823, CHANCE 6822-1/2 |
| RACK, TRANSFORMER, SINGLE | SEE SPECIFICATIONS |
| RACK, TRANSFORMER, TRIPLE MOUNT, BANDED | CHANCE C212-8006 |
| CLEVIS, SECONDARY/DE, INSUL 5/8 (3" SPOOL) | JOSLYN J1300, CHANCE 0327 |
| BRACKET, COMBINATION CUTOUT/ARRESTER 8" | CHANCE C206-0283 |
| CONDUCTOR, ALU, BARE, AA, DAHLIA, 556.5 | SEE SPECIFICATIONS |
| CONDUCTOR, ALU, BARE, AA, OXLIP, 4/0 | SEE SPECIFICATIONS |
| CONDUCTOR, CU BARE, SOL, HD, 4" | SEE SPECIFICATIONS |
| CONDUCTOR, TRIPLEX, INSL, CU, STR #2 | SEE SPECIFICATIONS |
| CONDUCTOR, TRIPLEX, INSL, CU, STR #4 | SEE SPECIFICATIONS |
| CONDUCTOR, TRIPLEX, INSL, CU, STR #6 | SEE SPECIFICATIONS |
| CONDUCTOR, DUPLEX, INSL, CU, STR#6 | SEE SPECIFICATIONS |
| SPLICE, TENSION, AUTO, ALU 477 - 556.5 | SEE SPECIFICATIONS |
| SPLICE, TENSION, AUTO, CU 4 SOL - 6 STR | SEE SPECIFICATIONS |
| SPLICE, TENSION, AUTO, CU 2 SOL - 3-4 STR | SEE SPECIFICATIONS |
| SPLICE, TENSION AUTO, CU 2/0 | SEE SPECIFICATIONS |
| CLAMP, DE, AUTO, ALU 4/0 - 3/0 | SEE SPECIFICATIONS |
| CLAMP, DE, AUTO, ALU 477 - 556.5 | SEE SPECIFICATIONS |
| CLAMP, DE, AUTO, CU, 6 SOL - 8 STR | SEE SPECIFICATIONS |
| CLAMP, DE, AUTO, CU, 2 SOL - 2-4 STR | SEE SPECIFICATIONS |
| CLAMP, HOT LINE, BRZ. 400 STR - 2 SOL | SEE SPECIFICATIONS |
| CLAMP, HOT LINE, BRZ. 400 STR - 6 SOL | SEE SPECIFICATIONS |
| CLAMP, STIRRUP, ALU, HDCU BAIL, #3-4/0 | SEE SPECIFICATIONS |
| CLAMP, GROUND ROD, 1/0-#8, 5/8" | JOSLYN J8492, CHANCE C208-0344 |

| | |
|--|----------------------------------|
| CLAMP, STRAIN STRAIGHT, BLTD, ALU 556.5 | SEE SPECIFICATIONS |
| CLAMP, PG ALU, 3-B, 397-556.5 397-556.5 | SEE SPECIFICATIONS |
| CLAMP, PG ALU, 1-B, 397-556.5 397-556.5 | SEE SPECIFICATIONS |
| CLAMP, STIRRUP, ALU, 556.5 | SEE SPECIFICATIONS |
| XFMR, POLE, 13.8/7.9 120/240 SB 15 KVA | SEE SPECIFICATIONS |
| XFMR, POLE, 13.8/7.9 120/240 SB 25 KVA | SEE SPECIFICATIONS |
| XFMR, POLE, 13.8/7.9 120/240 SB 37.5 KVA | SEE SPECIFICATIONS |
| XFMR, POLE, 13.8/7.9 120/240 SB 50 KVA | SEE SPECIFICATIONS |
| XFMR, POLE, 13.8/7.9 120/240 SB 75 KVA | SEE SPECIFICATIONS |
| XFMR, POLE, 13.8/7.9-120/240, SB 100 KVA | SEE SPECIFICATIONS |
| SWITCH, POLE TOP, GOAB, 25KV S&C OMNI RUPTER | SEE SPECIFICATIONS |
| CUT OUT, TYPE C, 100 AMPS, 15 KV, W/HDW | CHANCE C710-114PB, S&C 89021R9-B |
| FUSE HOLDER, 100 AMPS, CHANCE | SEE SPECIFICATIONS |
| FUSE LINK, TYPE T, RM HEAD, 3 AMP | CHANCE M3TA23 |
| FUSE LINK, TYPE T, RM HEAD, 8 AMP | CHANCE M8TA23 |
| FUSE LINK, TYPE T, RM HEAD, 10 AMP | CHANCE M10TA23 |
| FUSELINK, TYPE K, RM HEAD, 8 AMP | M8KA23 |
| FUSE LINK, TYPE K, RM HEAD, 6 AMP | M6KA23 |
| FUSE LINK, TYPE K, RM HEAD, 10 AMP | M10KA23 |
| ROD, GROUND, COPPERWELD, 5/8 X 5' | SEE SPECIFICATIONS |
| ARRESTER, 10 kV CLASS | SEE SPECIFICATIONS |
| ATCH, GUY STRAIN INSULATOR, 2 HOLE, 5/8 | JOSLYN P345DLT |
| PLATE, POLE EYE, 3/4" BOLTS, HEAVY DUTY | JOSLYN PX88, CHANCE GEP6 |
| ROD, ANCHOR, THIMBLE EYE, 5/8X8' | SEE SPECIFICATIONS |
| #8 COPPER SOLID SOFT DRAWN | SEE SPECIFICATIONS |
| STREET LIGHT, GALVANIZED ARMS | SEE SPECIFICATIONS |
| STREET LIGHT COBRA HEAD 150 WATTS | SEE SPECIFICATIONS |
| 150 WATT HIGH PRESSURE SODIUM LIGHT BULBS | SEE SPECIFICATIONS |
| LED STLIGHT FIXTURE W/PHOTO CELL LSR4 140 WATT | SEE SPECIFICATIONS |